



Certified to ISO
9001:2015,
without design

2998 Eastern Road • P.O. Box 1012 • Norton, Ohio 44203
(330) 825-4565 • Fax (330) 825-8699
WWW.ELSTONE.COM

THE FACTS

STONEKOTE®-50-GREEN or BLACK

CONFIDENTIALITY NOTICE: These documents contain confidential information belonging to the sender who is legally privileged. The information is intended only for the use of the individual or entity this is being sent to. If you are not the intended recipient, you are hereby notified that any disclosure, copying, distribution or the taking of any action in reliance on the contents of this information is strictly prohibited.

DESCRIPTION:

STONEKOTE®-50 is unique due to the fact that it is virtually a pure fluoropolymer.

USES:

STONEKOTE®-50 is recommended for "extreme use" applications, which require excellent nonstick or chemical resistance. In addition, it can be used continuously at 500°F (260°C) and intermittently at 550°F (290°C).

FDA STATUS:

STONEKOTE®-50 Black conforms with regulations governing use for direct food contact.

Guarantee of performance of applied coatings by E. L. Stone Company are neither implied nor expressed. E. L. Stone Company has no control over the myriad of possible service conditions (chemicals, temperatures, mixtures, etc.) E. L. Stone Company recommends that a test sample first be evaluated by the customer under conditions as close as possible to their intended service condition.

® REGISTERED SERVICE MARK OF E.L. STONE COMPANY, INC.